

OIL ONLY MELT BLOWN POLYPROPYLENE SORBENT

MATERIAL SAFETY DATA SHEET

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : White Oil-Only Melt Blown Sorbents

PRODUCT VARIATIONS : Used as absorbent pads, in absorbent pillows, absorbent socks and

booms

GENERAL USE : Designed for the clean-up of a hydrocarbon based spills including oil,

petrol and diesel.

CHEMICAL FAMILY : Olefin MANUFACTURER : SpillTech

IMPORTERS LOCATION : pH7, 4 Tawharau Lane, East Tamaki, Auckland 2013, New Zealand

CUSTOMER SERVICE TELEPHONE NUMBER : +64 9 263 3142 TECHNICAL INFORMATION TELEPHONE NUMBER : +64 9 263 3142

SECTION 2: HAZARD(S) IDENTIFICATION

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) RATING:

HEALTH: 0 FLAMMABILITY: 1 REACTIVITY: 0

*Not considered a hazardous material at temperatures below melting point. Not considered a controlled

substance or a carcinogen.

SECTION 3: COMPOSITION AND INFORMATION ON INGREDIENTS

INGREDIENTS PERCENT CAS NUMBER OSHA PEL ACGIH TLV Polypropylene 100% 9003-07-0 N/A N/A

SECTION 4: FIRST AID MEASURES

EYE CONTACT: Use eyewash, consult physician if accompanied by pain or irritation.

SKIN CONTACT: N/A INHALATION: N/A INGESTION: N/A

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT : 329°C AUTO IGNITION : 357°C FLAMMABLE LIMITS : N/A

FIRE EXTINGUISHING MEDIA : Water, Foam, CO2, Dry Chemical SPECIAL FIRE FIGHTING PROCEDURES : Standard procedures for Class A fires

UNUSUAL FIRE AND EXPLOSION HAZARDS: Some carbon monoxide formation is possible under oxygenlean conditions. Matting will not support combustion. Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous. Always refer to the MDS for the chemical absorbed before proceeding

SECTION 6: SPILLAGE, ACCIDENTAL RELEASE MEASURES

No special steps to be taken if material is spilled or released.

SECTION 7: HANDLING AND STORAGE

Store in dry area. Do not store near open flame, high heat, strong oxidants, or halogenated hydrocarbons.

Polypropylene, when heated, becomes very sticky and will burn. Use self-contained air masks to enter smoky area in the event of fire. Adequate ventilation is required to remove decomposition products when temperature exceeds melting point. Avoid contact with melted product.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous.

NOTE: Always refer to the SDS for the chemical absorbed before proceeding.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION EQUIPMENT

RESPIRATORY PROTECTION : None Required VENTILATION : None Required PROTECTIVE GLOVES : None Required

EYE PROTECTION : Safety glasses with side shields are recommended as a good practice for

industrial safety.

OTHER PROTECTIVE EQUIPMENT (SPECIFY): None Required

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR : White & virtually odour free

SPECIFIC GRAVITY : 0.88 - 0.92BOILING POINT (C) : Not Applicable MELTING POINT (C) :>160°C

SOLUBILITY IN WATER : Insoluble
% VOLATILE BY VOLUME : N/A
EVAPORATION RATE : N/A
VAPOR PRESSURE (mm Hg) : N/A
VAPOR DENSITY (Air = 1) : N/A

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL REACTIVITY : STABLE

HAZRADOUS REACTIONS : HAZARDOUS POLYMERISATION WILL NOT OCCUR

SECTION 11: TOXICOLOGICAL INFORMATION

HEALTH EFFECTS: Product is practically non-toxic and is unlikely to cause any skin irritation. In its

molten state the material will have a T° in excess of 150° C and will cause severe burns. Pre-existing eye and respiratory conditions may be aggravated by exposure

to material fines and fumes at processing T°.

INGESTION : Non-toxic

EYE : No hazard anticipated under normal conditions

SKIN : No hazard anticipated under normal conditions

INHALATION : No hazard anticipated under normal conditions

There is no release of any noxious fumes from polypropylene at ambient T°. If heated to T° above 250° C the fumes could be irritating to the respiratory system.

SECTION 12: ECOLOGICAL INFORMATION

NO DATA.

SECTION 13: DISPOSAL CONSIDERATIONS

Disposal must be done in accordance with local, state and federal regulations based on chemicals adsorbed by products.

Sorbents will take on the characteristics/properties of whatever liquid is absorbed. Therefore, all measures must be taken as if you were handling the liquid itself. Sorbents do not make the liquid less hazardous.

NOTE: Always refer to the SDS for the chemical absorbed before proceeding.

SECTION 14: TRANSPORT INFORMATION

DOT CLASSIFICATION: Non Hazardous

SECTION 15: REGULATORY INFORMATION

NO DATA.

SECTION 16: OTHER INFORMATION

The information contained herein is given in good faith, but no warranty, expressed or implied, is made.

DATE ISSUED : January 2007 UPDATED : November 2022

PREPARED BY: Dalton International Ltd Trading as pH7